Custom client advanced options

TABLE OF CONTENT

- Client features
- Client settings
- User interface settings
- Security settings
  - Permission Profiles (AnyDesk 7+)
  - Unattended Access settings (AnyDesk 7 and older)
  - Interactive Access / Accept window settings (AnyDesk 7 and older)
  - Discovery settings
  - Auto-disconnect settings
- Privacy settings
- Display settings
- Audio settings
- Connection settings
  - HTTP-Proxy settings
- File Transfer settings
- Recording settings
  - Automatic recording settings
  - Other settings
- VPN settings
- Wake-on-LAN settings
- Window positions and size (AnyDesk 7 and older)
- Disclaimer settings
- Layout settings (AnyDesk 6 and older)
- Address book
- Language codes

Other than the regular customization options, AnyDesk offers **Advanced** options to help users fine-tune their AnyDesk clients to their exact specifications.

You can either override a setting (meaning there is no way to change it back within AnyDesk) or change the default setting which AnyDesk uses. For security-related features, we recommend using “Override settings” so that they cannot be changed from the user interface of the custom client.

> 💡 **NOTE**
>
> Value possibilities in **bold** indicate the default setting.

 © 2026 www.somehelpwith.com

Client features

Feature	Key-value pair	Value possibilities
Use specific version	`_module=anydesk-<version>` Plain text Copy	**Example:** `_module=anydesk-9.0.7` Plain text Copy
Automatically register Alias	`ad.features.register_alias=true` Plain text Copy	**false**, true
Auto register Alias to custom namespace ⚠️ For custom Windows MSI installers, do **not** enable this in the client configurator (Hostname as Alias in my.anydesk II). This is applicable **only** for the Cloud solution; it is **not** needed for On-Premises clients.	`ad.anynet.register.add_to_namespace=true` Plain text Copy	**false**, true
Request elevation on startup (UAC)	`ad.features.auto_uac=true` Plain text Copy	**false**, true
Allow installation	`ad.features.install=true` Plain text Copy	false, **true**
Prevent users from removing the license	`ad.license.permissions=0` Plain text Copy	0: No permission **1: Has permission**
Disable Screen Recording feature (AnyDesk 9.0.0+)	`ad.features.screen_recording=false` Plain text Copy	false, **true**
Enable AnyDesk Assist feature (Ultimate-Cloud only, AnyDesk 9.0.0+)	`ad.session_queue.init=1` Plain text Copy	**0: Disable** 1: Enable
Enable Request Support feature (Ultimate-Cloud only, AnyDesk 9.0.0+)	`ad.session_queue.help_button=1` Plain text Copy	**0: Disable** 1: Enable
Disable Chat feature (AnyDesk 9.0.7+ for Windows)	`ad.features.session.chat=false` Plain text Copy	false, **true**

Client settings

Feature	Key-value pair	Value possibilities
Disable all settings	`ad.ui.cfg_enabled=false` Plain text Copy	false, **true**

User interface settings

Feature	Key-value pair	Value possibilities
Disable User Interface settings	`ad.ui.cfg_enable_interface=false` Plain text Copy	false, **true**
Set default language	`ad.ui.lang=<language>` Plain text Copy	See Language codes.
Disable auto-select language	`ad.ui.lang.auto=false` Plain text Copy	false, **true**
Disable invitation email option	`ad.ui.show_invite=false` Plain text Copy	false, **true**
Disable sending of direct invitations	`ad.features.session_invitation.send=false` Plain text Copy	false, **true**
Disable receiving of direct invitations	`ad.features.session_invitation.receive=false` Plain text Copy	false, **true**
Show AnyDesk ID instead of Alias *(AnyDesk 6 or older)*	`ad.ui.alias_or_id=true` Plain text Copy	**false**, true
Hide the AnyDesk ID and Alias	`ad.ui.hide_ad_id=1` Plain text Copy	**0: Disable** 1: Enable
Hide local taskbar when AnyDesk window is maximized	`ad.ui.maximize_type=true` Plain text Copy	**false**, true
Disable comment prompt on session close	`ad.ui.comment_session=false` Plain text Copy	false, **true**
Start AnyDesk in advanced view *(AnyDesk 4 or older)*	`ad.roster.adv_view=true` Plain text Copy	**false**, true
Remove the “What’s New” tile	`ad.ui.show_tile.whats_new=0` Plain text Copy	0: Disable **1: Enable**
Remove the AnyDesk Status tile	`ad.ui.show_tile.anydesk_status=false` Plain text Copy	false, **true**
Remove the Installation tile	`ad.ui.show_tile.install_anydesk=false` Plain text Copy	false, **true**
Remove “Set password for unattended access” tile *(Pre-AnyDesk 7)*	`ad.ui.show_tile.password=0` Plain text Copy	0: Disable **1: Enable**
Remove Discovery feature tile	`ad.discovery.show_tile=0` Plain text Copy	0: Disable **1: Enable**
Remove Telemetry Consent tile	`ad.ui.show_tile.telemetry=0` Plain text Copy	0: Disable **1: Enable**
Disable Recent Sessions	`ad.features.recent_out=0` Plain text Copy	0: Disable **1: Enable**
Disable Favorites	`ad.features.favorites=0` Plain text Copy	0: Disable **1: Enable**
Remove Retry Connection button	`ad.ui.show_retry_button=0` Plain text Copy	0: Disable **1: Enable**
Hide pie menu button on inactivity *(Android only)*	`ad.ui.auto_hide_nubsi=true` Plain text Copy	false, **true**
Hide plugin installation dialog *(Android only)*	`ad.ui.enable.dialog.plugin.install=0` Plain text Copy	0: Disable **1: Enable**
Hide plugin update dialog *(Android only)*	`ad.ui.enable.dialog.plugin.update=0` Plain text Copy	0: Disable **1: Enable**
Hide plugin activation dialog *(Android only)*	`ad.ui.enable.dialog.plugin.activation=0` Plain text Copy	0: Disable **1: Enable**

Hide battery optimization dialog *(Android only)*	`ad.ui.enable.dialog.battery_optimization=0` Plain text Copy	0: Disable **1: Enable**
Hide overlay permission dialog *(Android only)*	`ad.ui.enable.dialog.overlay_permission=0` Plain text Copy	0: Disable **1: Enable**
Hide scam warning dialog *(Android only)*	`ad.ui.enable.dialog.local_scam_warning=0` Plain text Copy	0: Disable **1: Enable**
Disable automatic tutorial start *(Android only)*	`ad.ui.enable.tutorial_autostart=0` Plain text Copy	0: Disable **1: Enable**
Hide privacy policy dialog *(Android only)*	`ad.ui.enable.dialog.privacy_policy=0` Plain text Copy	0: Disable **1: Enable**
Hide setup reminder dialog *(Android only)*	`ad.ui.enable.dialog.setup_prompt=0` Plain text Copy	0: Disable **1: Enable**

Security settings

Feature	Key-value pair	Value possibilities
Disable Security settings	`ad.ui.cfg_enable_security=false` Plain text Copy	false, **true**
Disable Access settings	`ad.ui.cfg_enable_access=false` Plain text Copy	false, **true**
Disable Permissions settings	`ad.ui.cfg_enable_permission_profiles=false` Plain text Copy	false, **true**
Disable interactive access ⚠️ ***By default, if AnyDesk is installed, the Accept Window always appears. When uninstalled, it appears only if an AnyDesk window is open.***	`ad.security.interactive_access=2` Plain text Copy	2: disable, **1: enable when AnyDesk is open**, **0: always enabled**
Enable Access Control List	`ad.security.acl_enabled=true` Plain text Copy	false, **true**
Define Access Control List Entries Specifies which AnyDesk IDs or aliases are allowed when ACL is enabled.	`ad.security.acl_list=<ID>:true; <Alias>:true;` Plain text Copy	`123456789:true; mycomputer@ad:true;`
Disable unattended access	`ad.features.unattended=false` Plain text Copy	false, **true**
Forbid others to save login information for this computer	`ad.security.allow_logon_token=false` Plain text Copy	false, **true**
Disable Two-Factor-Authentication	`ad.features.two_factor_auth=false` Plain text Copy	false, **true**
Disable File Manager sessions	`ad.features.file_manager=false` Plain text Copy	false, **true**
Show list of logged in users (Windows Server only)	`ad.security.connect.send_user_list=1` Plain text Copy	0: Disable, **1: Enable**
Disable clipboard sync, even with remote endpoint permission.	`ad.security.frontend_clipboard=0` Plain text Copy	0: Disable, **1: Enable**
Disable clipboard files sync, even with remote endpoint permission.	`ad.security.frontend_clipboard_files=0` Plain text Copy	0: Disable, **1: Enable**
Disable lock account on session end even with remote endpoint permission	`ad.security.sess.lock_remote_account=0` Plain text Copy	**0: Disable,** 1: Enable
Terminate existing incoming sessions when receiving a session request (Android only)	`ad.security.kickout=1` Plain text Copy	0: Disable, **1: Enable**
Protect settings with device or biometric credentials (Android only)	`ad.security.settings_protection=2` Plain text Copy	0: Disable, **2: Enable**

Permission Profiles (AnyDesk 7+)

> 💡 **NOTE**
>
> Use the **Permission Profile Key-Value Pair Generator** to create key-value pairs for your custom configuration.

> 🚨 **IMPORTANT**
>
> Permission profiles (introduced in AnyDesk 7) offer more flexibility than the older `ad.security` key-value pairs.
>
> You can create up to 10 custom profiles. Each profile can have its own permissions and unattended access settings. Permissions are split between:
>
> - The **Accept Window**
> - **Settings > Access**
>
> **Example**
>
> To disable audio transmission by default when `profile1` is used:
>
> `ad.security.permission_profiles.profile1.permissions.audio=0`
>
> Plain text
>
> Copy
>
> To stop the remote user from changing this in the Accept Window:
>
> `ad.security.permission_profiles.profile1.changeable_in_accept_window.audio=0`
>
> Plain text
>
> Copy

Feature	Key-value pair	Value possibilities
Profile identifiers	`<profile_id>` Plain text Copy	`Default: _default _full_access _screen_sharing _unattended_access Custom: profile1 to profile10` Pla Copy
Permissions list	`<permission>` Plain text Copy	`audio input clipboard clipboard_files block_input sa restart file_manager lock_desk sysinfo whiteboard tcp_tunnel vpn user_pointer privacy_feature record_s logoff_session` Plain text Copy
Enable session profile memory	`ad.security.permission_profiles.enable_previous_session=1` Plain text Copy	0: No, **1: Yes**
Define profile name	`ad.security.permission_profiles.define.<profile_id>=<name>` Plain text Copy	**Example:** `ad.security.permission_profiles.define.profile1=myp` Plain text Copy
Disable permission in Settings	`ad.security.permission_profiles.<profile_id>.permissions. <permission>=0` Plain text Copy	0: Disabled, 1: Enabled
Disable permission change via Accept Window	`ad.security.permission_profiles. <profile_id>.changeable_in_accept_window.<permission>=0` Plain text Copy	0: Not changeable, **1: Changeable**
Allow profile switching	`ad.security.permission_profiles. <profile_id>.can_switch_profile=1` Plain text Copy	0: No, **1: Yes**
Show profile in Accept Window	`ad.security.permission_profiles. <profile_id>.show_in_accept_window=1` Plain text Copy	0: No, **1: Yes**
Set unattended access password	`ad.security.permission_profiles.<profile_id>.pwd=<hash>` Plain text Copy `ad.security.permission_profiles. <profile_id>.salt=<salt>` Plain text Copy	Leave “pwd” empty to disable. Hash and salt can be generate the Password Generator in my.anydesk II > Builds > Utilities.
Remove profile from custom client	`ad.security.permission_profiles.<profile_id>.removed=1` Plain text Copy	0: No, **1: Yes**
Allow manual profile creation	`ad.security.permission_profiles.can_create=1` Plain text Copy	0: No, **1: Yes**
Global permissions (Settings) Applies to all profiles.	`ad.security.permission_profiles.permissions.<permission>=1` Plain text Copy	0: Disabled, 1: Enabled
Global permissions (Accept	`ad.security.permission_profiles.changeable_in_accept_window. <permission>=1` Plain text Copy	0: Not changeable, 1: Changeable

Feature	Key-value pair	Value possibilities
Window) Applies to all profiles.		
Global profile switching Applies to all profiles.	`ad.security.permission_profiles.can_switch_profile=1` Plain text Copy	0: No, 1: Yes
Global profile visibility in Accept Window Applies to all profiles.	`ad.security.permission_profiles.show_in_accept_window=1` Plain text Copy	0: No, 1: Yes

Unattended Access settings (AnyDesk 7 and older)

> 🚨 **IMPORTANT**
>
> In AnyDesk 7 and later, the key-value pairs listed here apply to the **Unattended Access** profile **only if** it has been explicitly configured in the custom client. These settings control which permissions are available during unattended access sessions.
>
> They only take effect if the following key is set:
>
> `ad.security.enable_uaccess_permissions=true`
>
> Plain text
>
> Copy
>
> Also, make sure custom permissions for unattended access are defined.

Enable unattended access-specific permissions

Feature	Key-value pair	Value possibilities
Disable standard permissions for unattended access (AnyDesk 6 for Windows and older)	`ad.security.enable_uaccess_permissions=false` Plain text Copy	false, **true**

Permission controls for unattended access

Feature	Key-value pair	Value possibilities
Allow hearing computer's audio	`ad.security.uaccess.hear_audio=true` Plain text Copy	false, true
Allow control of keyboard and mouse	`ad.security.uaccess.control_input=true` Plain text Copy	false, true
Allow access to clipboard content	`ad.security.uaccess.sync_clipbrd=true` Plain text Copy	false, true
Allow file transfers via clipboard	`ad.security.uaccess.clipboard.files=true` Plain text Copy	false, true
Allow keyboard and mouse to be locked	`ad.security.uaccess.block_input=true` Plain text Copy	false, true
Allow system restart	`ad.security.uaccess.restart=true` Plain text Copy	false, true
Allow use of file manager	`ad.security.uaccess.file_manager=true` Plain text Copy	false, true
Lock desktop after session ends	`ad.security.uaccess.lock_account=true` Plain text Copy	false, true
Allow system information request	`ad.security.uaccess.sysinfo=true` Plain text Copy	false, true
Allow remote printing	`ad.security.uaccess.print=true` Plain text Copy	false, true
Allow screen annotations (whiteboard)	`ad.security.uaccess.whiteboard=true` Plain text Copy	false, true
Allow TCP tunnel creation	`ad.security.uaccess.tcp_tunnel=true` Plain text Copy	false, true
Enable privacy mode	`ad.security.uaccess.privacy_feature=true` Plain text Copy	false, true
Show a colored pointer during blocked input	`ad.security.uaccess.user_pointer=true` Plain text Copy	false, true

Interactive Access / Accept window settings (AnyDesk 7 and older)

These key-value pairs control permissions during interactive sessions for versions prior to AnyDesk 7. Use them to restrict what remote users can do during a session initiated via the Accept Window.

Feature	Key-value pair	Value possibilities
Allow hearing computer's audio	`ad.security.hear_audio=true` Plain text Copy	false, true
Allow control of keyboard and mouse	`ad.security.control_input=true` Plain text Copy	false, true
Allow access to clipboard content	`ad.security.sync_clipbrd=true` Plain text Copy	false, true
Allow file transfers via clipboard	`ad.security.clipboard.files=true` Plain text Copy	false, true
Allow keyboard and mouse to be locked	`ad.security.block_input=true` Plain text Copy	false, true
Allow system restart	`ad.security.restart=true` Plain text Copy	false, true
Allow use of file manager	`ad.security.file_manager=true` Plain text Copy	false, true
Allow system information request	`ad.security.sysinfo=true` Plain text Copy	false, true
Allow remote printing	`ad.security.print=true` Plain text Copy	false, true
Allow screen annotations (whiteboard)	`ad.security.whiteboard=true` Plain text Copy	false, true
Allow TCP tunnel creation	`ad.security.tcp_tunnel=true` Plain text Copy	false, true
Enable privacy mode	`ad.security.privacy_feature=true` Plain text Copy	false, true
Show colored pointer during blocked input	`ad.security.user_pointer=true` Plain text Copy	false, true

Discovery settings

These key-value pairs control how the Discovery feature behaves in AnyDesk, including network visibility, multicast communication, and participation settings.

Configuration options

Feature	Key-value pair	Value possibilities
Disable the Discovery feature entirely	`ad.features.discovery=false` Plain text Copy	false, **true**
Disable scanning the local network for other clients	`ad.discovery.default_behavior=0` Plain text Copy `ad.discovery.enabled=false` Plain text Copy	0: Disabled 1: **Enabled** false, **true**
Exclude this device from being discoverable	`ad.discovery.hidden=false` Plain text Copy	false, **true**
Set the IP address used for multicast communication	`ad.discovery.multicast_ip=<ip>` Plain text Copy	e.g. **239.255.102.18**
Set the port used for multicast communication	`ad.discovery.multicast_port=<port>` Plain text Copy	e.g. **50001**
Define the number of UDP ports to use, starting from ad.discovery.multicast_port	`ad.discovery.port_range=<number>` Plain text Copy	e.g. 1, 2, 3

Auto-disconnect settings

These key-value pairs control the automatic disconnection behavior for inactive remote sessions in AnyDesk.

Feature	Key-value pair	Value possibilities
Enable auto-disconnect	`ad.security.auto_disconnect.mode=1` Plain text Copy	**0: Disabled** 1: Enabled
Set timeout duration before auto-disconnect (in seconds)	`ad.security.auto_disconnect.timeout=<number>` Plain text Copy	Minimum: 60

Privacy settings

These key-value pairs control display and privacy features in AnyDesk, including visible identity, background previews, chat logs, and screen framing.

Feature	Key-value pair	Value possibilities
Disable privacy settings	`ad.ui.cfg_enable_privacy=false` Plain text Copy	false, **true**
Set custom displayed username	`ad.privacy.name.show=1` Plain text Copy	**1: Account username** 2: Custom username
Enter custom username (when using custom type)	`ad.privacy.name=<string>` Plain text Copy	Example: user1
Hide displayed user image	`ad.privacy.image.show=0` Plain text Copy	0: Hide image **1: Show account image**
Hide background in desk preview	`ad.privacy.bkgnd.show=3` Plain text Copy	0: Screenshot **1: Wallpaper** 3: Disabled
Choose custom screenshot path	`ad.privacy.scrshot.path_cfg=2` Plain text Copy	**1: Default** 2: Custom
Set a custom screenshot path	`ad.privacy.scrshot.path=<path>` Plain text Copy	Absolute paths only. Example: C:\Users<username>...
Set chat log storage location	`ad.privacy.chat.path_cfg=2` Plain text Copy	0: Disabled **1: Default path** 2: Custom path
Set a custom chat log path	`ad.privacy.chat.path=<path>` Plain text Copy	Example: C:\Users<username>...
Enable alternative screen background (ASB) color ***No longer available with AnyDesk 9 and newer***	`ad.privacy.wallpaper.mode=1` Plain text Copy	**0: Disabled** 1: Color
Set ASB color ***No longer available with AnyDesk 9 and newer***	`ad.privacy.wallpaper.color=<RGB_HEX>` Plain text Copy	**Default: #000000FF**
Enable screen frame overlay	`ad.privacy.screen_frame.mode=1` Plain text Copy	**0: Disabled** 1: Enabled
Set screen frame width (pixels)	`ad.privacy.screen_frame.width=<number>` Plain text Copy	Range: 5–20 **Default: 10**
Set screen frame opacity (alpha)	`ad.privacy.screen_frame.opacity=<number>` Plain text Copy	Range: 51–255 **Default: 128**
Set screen frame color (RGBA hex)	`ad.privacy.screen_frame.color=<RGBA_HEX>` Plain text Copy	**Default: #FF0000FF**

Display settings

These key-value pairs control how visual elements are rendered in AnyDesk, including video quality, cursor visibility, screen mode, rendering methods, and session behavior.

Feature	Key-value pair	Value possibilities
Disable display settings	`ad.ui.cfg_enable_video=false` Plain text Copy	false, true
Set display quality preference	`ad.image.quality_preset=<value>` Plain text Copy	0: Best quality 1: Balanced 2: Optimize response time
Choose remote cursor behavior	`ad.image.show_remote_cursor_option=<value>` Plain text Copy	0: Hide cursor 1: Show cursor always 2: Show cursor only on movement
Show move/resize helper overlay	`ad.image.move_size_hlp=true` Plain text Copy	**false**, true
Prevent hotkey transmission to the remote device	`ad.image.suppress_keys=true` Plain text Copy	**false**, true
Choose view mode scaling	`ad.image.viewmode=<value>` Plain text Copy	0: Original size **1: Shrink** 2: Stretch
Start new sessions in fullscreen	`ad.image.insta_fullscreen=true` Plain text Copy	**false**, true
Enable edge scrolling in original view mode	`ad.image.edge_scroll=true` Plain text Copy	**false**, true
Select full-screen mode behavior	`ad.image.fullscreen_mode=<value>` Plain text Copy	**0: Exclusive** 1: Windowed
Choose rendering method	`ad.image.rendermode=<value>` Plain text Copy	0: Disabled 1: DirectDraw **2: Direct3D** 3:OpenGL
Disable saving display settings between sessions	`ad.session.remember_settings=false` Plain text Copy	false, **true**

Audio settings

Use the following key-value pairs to configure audio behavior for AnyDesk sessions, including transmission and playback modes.

Feature	Key-value pair	Value possibilities
Disable audio settings	`ad.ui.cfg_enable_audio=false` Plain text Copy	false, **true**
Set audio transmission mode	`ad.audio.transmit_mode=<value>` Plain text Copy	0: Disabled **1: Standard** 2: Transmit audio output 3: Specify manually
Set audio playback mode	`ad.audio.playback_mode=<value>` Plain text Copy	0: Disabled **1**: **Standard** 3: Specify manually
Enable exclusive audio playback	`ad.audio.exclusive=true` Plain text Copy	**false**, true

Connection settings

Use the following key-value pairs to configure network connection parameters, including direct connection behavior, session limits, and proxy settings.

Feature	Key-value pair	Value possibilities
Disable connection settings	`ad.ui.cfg_enable_connection=false` Plain text Copy	false, **true**
Disable direct connections	`ad.anynet.direct=false` Plain text Copy	false, **true**
Set the listening port	`ad.anynet.listen_port=<port>` Plain text Copy	**Default: 7070**
Limit incoming sessions	`ad.session.limit_incoming=<number>` Plain text Copy	Example: 1, 2, 3, …
Limit outgoing sessions	`ad.session.limit_outgoing=<number>` Plain text Copy	Example: 1, 2, 3, …

HTTP-Proxy settings

Feature	Key-value pair	Value possibilities
Force use of proxy	`ad.anynet.proxy.mandatory=true` Plain text Copy	**false**, true
Set proxy mode	`ad.anynet.proxy.mode=<mode>` Plain text Copy	0: Never use a proxy 1**: Auto-detect** 2**:** Use a specific proxy
Set proxy type	`ad.anynet.proxy.type=<type>` Plain text Copy	**0: HTTP** 1**:** SOCKS
Ask for proxy authentication	`ad.anynet.proxy.auth=true` Plain text Copy	**false**, true
Automatically detect proxy authentication	`ad.anynet.proxy.auto_auth=true` Plain text Copy	false, **true**

NTLM authentication

Feature	Key-value pair
Configure NTLM authentication	`ad.anynet.proxy.mandatory=true ad.anynet.proxy.auth=false ad.anynet.proxy.auto_auth=true` Plain text Copy

File Transfer settings

Feature	Key-value pair	Value possibilities
Disable File Transfer settings	`ad.ui.cfg_enable_filetransfer=false` Plain text Copy	false, **true**

Recording settings

Feature	Key-value pair	Value possibilities
Disable session recording feature	`ad.features.sess_record=false` Plain text Copy	false, **true**
Disable access to session recording settings	`ad.ui.cfg_enable_recording=false` Plain text Copy	false, **true**
Disable session playback	`ad.features.sess_playback=false` Plain text Copy	false, **true**

Automatic recording settings

Description	Key-value pair	Value possibilities
Start recording for all sessions (non-Windows and Windows < 6.1.0)	`ad.recording.auto_start=true` Plain text Copy	**false**, true
Start recording when an incoming session starts and the user is logged out (Windows ≥ 6.1.0)	`ad.recording.auto_start.incoming.admin=1` Plain text Copy	**0: Disabled**, 1: Enabled
Start recording when an incoming session starts and the user is logged in (Windows ≥ 6.1.0)	`ad.recording.auto_start.incoming=1` Plain text Copy	**0: Disabled**, 1: Enabled
Start recording for outgoing sessions (Windows ≥ 6.1.0)	`ad.recording.auto_start.outgoing=1` Plain text Copy	**0: Disable**d, 1: Enabled

Other settings

Description	Key-value pair	Value possibilities
Prevent remote users from recording the session	`ad.security.record_session=false` Plain text Copy	false, **true**
Set session recording path configuration	`ad.recording.path_cfg=2` Plain text Copy	**1: Default path**, 2: Custom path
Specify custom recording path	`ad.recording.path=<path>` Plain text Copy	e.g., C:\Recordings

VPN settings

Feature	Key-value pair	Value possibilities
Disable the VPN feature	`ad.features.vpn=false` Plain text Copy	false, **true**
Disable access to VPN settings	`ad.ui.cfg_enable_vpn=false` Plain text Copy	false, **true**

Wake-on-LAN settings

Feature	Key-value pair	Value possibilities
Disable the Wake-on-LAN feature	`ad.features.wol=false` Plain text Copy	false, **true**
Disable access to Wake-on-LAN settings	`ad.ui.cfg_enable_wol=false` Plain text Copy	false, **true**

Window positions and size (AnyDesk 7 and older)

Feature	Key-value pair	Value possibilities
Start AnyDesk in a maximized window	`ad.ui.main_win.max=true` Plain text Copy	**false**, true
Set the horizontal position of the left window border	`ad.ui.main_win.x=<pixels>` Plain text Copy	Value in pixels, e.g. 100
Set the vertical position of the top window border	`ad.ui.main_win.y=<pixels>` Plain text Copy	Value in pixels, e.g. 100
Set the window width	`ad.ui.main_win.width=<pixels>` Plain text Copy	Minimum: 900, e.g. 1000
Set the window height	`ad.ui.main_win.height=<pixels>` Plain text Copy	Minimum: 720, e.g. 1000

Disclaimer settings

Feature	Key-value pair	Value possibilities
Set the disclaimer title	`ad.ui.disclaimer.title=<text>` Plain text Copy	Replace with your custom title
Set the disclaimer body text	`ad.ui.disclaimer.text=<text>` Plain text Copy	Replace with your custom message
Set the text for the accept button	`ad.ui.disclaimer.accept=<text>` Plain text Copy	Replace with button label
Set the text for the cancel button	`ad.ui.disclaimer.cancel=<text>` Plain text Copy	Replace with button label
Set the text and title color	`ad.ui.disclaimer.text.color=<HTML color code>` Plain text Copy	e.g. #FFFFFF
Set the background color	`ad.ui.disclaimer.bg.color=<HTML color code>` Plain text Copy	e.g. #FFFFFF
Display a session disclaimer for interactive access	`ad.session_warning.show=1` Plain text Copy	0: No, 1: Yes
Require a 10-second delay before the disclaimer can be accepted	`ad.session_warning.timeout_mode=1` Plain text Copy	0: No, 1: Yes
Set the session disclaimer message	`ad.session_warning.msg=<text>` Plain text Copy	Replace with your custom message

Layout settings (AnyDesk 6 and older)

Feature	Key-value pair	Value possibilities
Change the label for “This Desk”	`ad.ui.id_group.title=<text>` Plain text Copy	`<text>` : Custom label text
Replace the description under “This Desk”	`ad.ui.id_group.text=<text>` Plain text Copy	`<text>` : Custom description text
Change the label for “Remote Desk”	`ad.ui.connect_group.title=<text>` Plain text Copy	`<text>` : Custom label text
Replace the description under “Remote Desk”	`ad.ui.connect_group.text=<text>` Plain text Copy	`<text>` : Custom description text

Address book

Feature	Key-value pair	Value possibilities
Disable Address Book	`ad.features.address_book=false` Plain text Copy	`false` , `true`
Choose Address Book view type	`ad.abook.view_type=0` Plain text Copy	`0` : Default `1` : List `2` : Big Tiles `4` : Small Tiles
Automatically tag entries added via “Add to Address Book” option	`ad.anynet.register.roster_tags=<text>` Plain text Copy	`<text>` : Custom tag(s) to be applied automatically

Language codes

Language	ISO code
Bulgarian	`bg` Plain text Copy
Croatian	`hr` Plain text Copy
Czech	`cz` Plain text Copy
Danish	`da` Plain text Copy
Dutch	`nl` Plain text Copy
English	`en` Plain text Copy
Estonian	`et` Plain text Copy
Finnish	`di` Plain text Copy
French	`fr` Plain text Copy
German	`de` Plain text Copy
Greek	`el` Plain text Copy
Hungarian	`hu` Plain text Copy
Italian	`it` Plain text Copy
Japanese	`ja` Plain text Copy
Korean	`ko` Plain text Copy
Norwegian	`no` Plain text Copy
Polish	`pl` Plain text Copy
Portuguese	`pt` Plain text Copy
Portuguese (Brazil)	`pt-br` Plain text Copy
Romanian	`ro` Plain text Copy
Russian	`ru` Plain text Copy
Simplified Chinese	`zh` Plain text Copy
Slovak	`sk` Plain text Copy
Spanish	`es` Plain text Copy
Swedish	`sv` Plain text Copy
Traditional Chinese	`zh-cl` Plain text Copy
Turkish	`tr` Plain text Copy
Ukrainian	`uk` Plain text Copy